

III. SPECIFICATION AMENDMENTS

On page 12, please replace paragraph [0032] as rewritten below:

[0032] Source URI of the Management Server (Source URI). The field contains the URI identifier of the server, e.g. ~~'http://www.syncml.org/ngmt-server'~~. In certain cases, this field can also be shortened by leaving out the protocol identifier, for instance, or, instead of the server address, transmitting only the shorter identifier in the field. Alternatively, the TASS field can be used for transmitting the server identifier.

Please replace the Abstract on page 21 as rewritten below:

A method of starting a session in a synchronization system. The maximum size of a message that is to be sent from a synchronization server to a mobile station for the request, and coding instructions, by which at least one of the identifiers can be coded into a bit sequence requiring substantially fewer bits than its ASCII presentation, are determined in the synchronization server. Decoding instructions, by means of which the original identifier is obtained from the bit sequence, are determined in the mobile station. When the purpose is to transmit a request indicating the need for starting a session to at least one mobile station, a message is formed, is shorter or as long as ~~said the~~ maximum size and ~~comprises~~ includes the pre-selected identifiers, at least one of which is presented as a bit sequence defined according to the coding instructions. The mobile station forms a session initialization message on the basis of the information included in the message received from the server, at least part of information being defined from the

received bit sequence according to ~~said~~ the decoding
instructions.

~~(Figure 3)~~